



MATERIAL SAFETY DATA SHEET

ECOBLANKET / ECOBERM

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	EcoBlanket / EcoBerm
Product Code	-
Other Names	-
Product Use	Compost blanket for erosion control
Supplier Name	Treline Pty Ltd trading as The Hills Bark Blower
Address	Corner Annangrove and Sedger Roads Kenthurst NSW 2156
Telephone Number	02 9654 2288
Emergency Telephone	1300 BLOWIT

2. HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE. NON DANGEROUS GOODS.

Classified as hazardous according to the criteria of Safe Work Australia.

Hazards	Xn - Harmful
Risk Phrases	R20 - Harmful by inhalation. R42 - May cause sensitisation by inhalation. R43 - May cause sensitisation by skin contact.
Safety Phrases	S22 - Do not breathe dust. S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection. S38 - In case of insufficient ventilation, wear suitable respiratory equipment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient (common name)	CAS Number	Percentage
Compost, mulches and other organic gardening material	Not applicable	40%
Clinker ash (which consist mostly of silicon dioxide present in two forms: amorphous, which is rounded and smooth, and crystalline, which is sharp, pointed and hazardous, aluminium oxide and iron oxide)	Not applicable	10%
Raw pine bark	Not applicable	20%
Composted hardwood sawdust	Not applicable	30%

4. FIRST AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist.
Ingestion	If swallowed immediately rinse mouth with water. Give plenty water to drink. Never give anything by mouth to an unconscious person. Seek immediate medical attention.
Skin	If skin or hair contact occurs, immediately remove contaminated clothing and wash skin and hair thoroughly with soap and plenty of water. Seek medical attention if symptoms persist. Launder protective clothing before re-use.
Eyes	If in eyes, hold eyelids apart and flush the eye continuously with large amounts of water for at least 15 minutes. Seek medical attention if symptoms persist.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	For major fires call the Fire Brigade. Ensure that an escape path is available from any fire. Water spray.
Hazardous Combustion Products	No information available.
Firefighting Equipment	Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.
Unusual Fire or Explosion Hazards	Non-combustible material.
Hazchem Code	Not allocated.

6. ACCIDENTAL RELEASE MEASURES

Spills	In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection, a P1 or P2 particulate respirator (dust mask) and impervious elbow-length gloves. Evacuate general area and deny access to unnecessary and unprotected personnel. Spilled area should be wet down with water to reduce dust generation before cleanup. If unable to reuse or recycle, dispose of waste materials according to applicable local and state government regulations.
---------------	---

7. HANDLING AND STORAGE

Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including
-----------------	--

washing hands before eating. Provide adequate ventilation. Avoid inhaling dust which can be generated during processing, handling and storage. Use a P1 or P2 particulate respirator (dust mask).

Storage

Store in a cool, dry area. Avoid generating and inhaling dust.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Standards
(Safe Work Australia)**

Aluminium oxide:
TWA: - ppm / 10 mg/m³
STEL: - ppm / - mg/m³

Fumed silica (respirable dust):
TWA: - ppm / 2 mg/m³
STEL: - ppm / - mg/m³

Quartz (crystalline silica):
TWA: - ppm / 0.1mg/m³
STEL: - ppm / - mg/m³

Titanium dioxide:
TWA: - ppm / 10 mg/m³
STEL: - ppm / - mg/m³

Nickel (metal):
TWA: - ppm / 1mg/m³
STEL: - ppm / - mg/m³

Nickel (soluble compounds as Ni)
TWA: - ppm / 0.1 mg/m³
STEL: - ppm / - mg/m³

Engineering Controls

Local exhaust ventilation is recommended when vapours can be released in excess of established airborne exposure limits.

Respiratory Protection

If exposed to dust wear a Safe Work Australia approved P1 or P2 particulate respirator (dust mask). See Australian Standards AS/NZS 1715 and 1716 for more information.

Eye Protection

Non-fogging dust resistant goggles or safety glasses. See Australian Standards AS 1336 and AS/NZS 1337 for more information.

Skin Protection

Wear standard duty gloves, loose, comfortable protective clothing and boots. See Australian Standards AS 2161 and 2919 and AS/NZS 2210 for more information.

Hygienic Practices

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Brown to grey blend of natural organic and mineral substances
Odour	Non specific earthy odour
Solubility in Water	Insoluble
pH	No information available
Boiling Point	Not applicable
Melting Point	Not applicable
Vapour Pressure	Not applicable
Specific Gravity (H₂O=1)	No information available
Evaporation Rate (H₂O=1)	Not applicable
Flash Point (Closed Cup)	Not applicable
Flammable Limit – Lower	Not applicable
Flammable Limit – Upper	Not applicable
Auto-ignition Temperature	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability	Stable.
Incompatible Materials	No information available
Hazardous Decomposition Products	No information available
Hazardous Polymerization	Will not occur.
Conditions to Avoid	No information available

11. TOXICOLOGICAL INFORMATION

Toxicity	<p>Clinker ash contains crystalline silica. Inhaling dust generated during handling may cause scarring of the lung (silicosis), lung cancer and chronic bronchitis. It also may increase the risk of scleroderma (thickening of the connective tissue) and kidney disease (increased prevalence of renal abnormalities and end stage – renal disease – glomerulonephritis).</p> <p>Clinker ash also contains environmental toxins in significant amounts, including arsenic (43.4 ppm); barium (806 ppm); beryllium (5 ppm); boron (311 ppm); cadmium(3.4 ppm); chromium (136 ppm); chromium VI (90 ppm); cobalt (35.9 ppm); copper (112 ppm); fluorine (29 ppm); lead (56 ppm); manganese (250 ppm); nickel (77.6 ppm); selenium (7.7 ppm); strontium (775 ppm); thallium (9</p>
-----------------	---

ppm); vanadium (252 ppm); and zinc (178 ppm).

Compost (mulch) is made from organic materials, including composted pine bark, and contains living micro-organisms, including bacteria, fungi and protozoa. May also contain mineral and fertiliser additives. Inhalation of dust and/or liquid mists may irritate, inflame or sensitise the nose, throat and lungs resulting in illnesses ranging from hay fever or asthma, to pneumonia (eg Legionnaire's disease) or pneumonia-like illnesses. Direct contact with this material or its dust and/or liquid mists (bio-aerosols) may cause skin irritation (dermatitis), and skin or eye infection or irritation.

Routes of Exposure

Inhalation, ingestion, eye and skin

Acute Health Effects

Inhalation: May cause irritation, inflammation and sensitisation of the nose, throat and lungs.

Ingestion: Unlikely under normal conditions, but swallowing this product will result in abdominal discomfort and increase the risk of gastro-intestinal infections.

Eye: May cause irritation resulting in redness and watering or even eye infection.

Skin: May cause irritation and in some people may lead to skin sensitisation, dermatitis or skin infection.

Chronic Health Effects

Repeated inhalation of dust (bio-aerosols) from these products may result in respiratory irritation, inflammation or sensitisation resulting in illnesses ranging from hay fever and asthma to pneumonia (eg Legionnaire's disease) and pneumonia-like illnesses.

It may also cause scarring of the lung (silicosis), lung cancer, chronic bronchitis and increase the risk of scleroderma (thickening of the connective tissue) and kidney disease.

All people working with these and other landscaping and horticultural products should ensure that they are adequately protected from tetanus.

Existing Conditions Aggravated by Exposure Carcinogenicity

Pre-existing respiratory diseases.

The International Agency for Research on Cancer (IARC) has classified crystalline silica as a Type 1 carcinogen - Carcinogenic to humans, based on sufficient evidence in humans and animals.

12. ECOLOGICAL INFORMATION

**Ecotoxicity
Mobility**

No information available.
No information available.



MATERIAL SAFETY DATA SHEET

13. DISPOSAL CONSIDERATIONS

Disposal methods and containers Dispose according to applicable local and state government regulations.
Special precautions for landfill or incineration Please consult your state Land Waste Management Authority for more information.

14. TRANSPORT INFORMATION

Not classified as a dangerous good according to the Australian Code for the Transport of Dangerous goods by road or rail.

UN Number Not applicable
Proper Shipping Name Not applicable
Dangerous Goods Class Not applicable
Hazchem Code Not applicable
Packing Group Not applicable
Special Precautions Not applicable

15. REGULATORY INFORMATION

Silicon dioxide is listed in the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Last Revision of MSDS Rev 1.0 (07/03/2011)
Prepared by MSDS.COM.AU Pty Ltd www.msds.com.au
Abbreviations Used IARC: International Agency for Research on Cancer
NTP: National Toxicology Program (U.S.)
OSHA: Occupational Safety and Health Administration (U.S.)
STEL: Short term exposure limit
TWA: Time weighted average

Emergency Contacts

Tremline Pty Ltd trading as The Hills Bark Blower 02 9654 2288
Tremline Pty Ltd trading as The Hills Bark Blower – Emergency Number 1300 BLOWIT
Police and Fire Brigade 000
Poisons Information Centre 13 11 26



MATERIAL SAFETY DATA SHEET

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Tremline Pty Ltd trading as The Hills Bark Blower makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.

Please read instructions / label before using product.

This MSDS is prepared in accord with the Safe Work Australia document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]